



AD 430

Reliable Drying Performance

- Energy-saving rotary piston compressor
- Large water tank with automatic shut-off when full
- Built-in hygostat
- Operating hours counter
- Air filter
- Quiet operation



Environmentally friendly,
high-performance air dehumidifiers –
equipped with the new technology.

Type

AD 430

Recommended Coverage (Indicative)*	cu.ft	4000
Extraction (30 °C/80% RH)	1/24 hr	30.5 l /24 hr
De-humidifying performance/ power consumption at**		
30°C/80% RH	1/24 h	30.5 l / 540 Watt
20°C/60% RH	1/24 h	12.0 l / 400 Watt
10°C/70% RH	1/24 h	08.0 l / 320 Watt
Max. power consumption	Watt	540
Air circulation rate	m ³ /h	Speed 1 = 500 cbm/h
	m ³ /h	Speed 2 = 625 cbm/h
Working temperature range	°C	5°C to 32°C
Noise Level	dB	51
Power supply	V/Hz	230V/50Hz
Dimension (height/width/depth)	Inches	23" x 13" x 15"
Weight	Kg	21
Arrangement		On the Ground
Coolant		R407c
Condensate drainage		Water Tank (8.3l) or Hose connector
Maintenance required		Empty bucket, clean/change air filter
Timer (Optional)		Yes

*Guideline figures/based on experience • **Based on DIN EN 810
• Subject to technical changes • Made in Germany