



## ND 316 Precise and Efficient

Novita dehumidifier ND 316 comes with a soft key control panel that allows you to choose your desired humidity level and extraction rate. You can also choose to delay the start up or switch off your ND 316 with a programmable timer. With the help of internal diagnostic, the "Liquid Crystal Display" allows you to clearly view the humidity and temperature reading along with your other settings. Precise and Efficient, the ND 316 is ideal for the detailed.

Type	ND 316
Power consumption	320 watts
Extraction	16 litres/day (30°C,80% RH)
Running Temperature	5°C-35° C
Compressor	Rotary
Coolant	R-410a
Empty Weight	13kg
Dimension (WxDxH) in.	13 x 9 x 22
Recommended Coverage ( Indicative )	Upto 2500 cu. ft.
Tank Capacity	3 litres
Air flow	150m <sup>3</sup> /hr
Humidity Setting	Available
Optional Product Accessory	PVC Hose Activated Carbon Charcoal Filter
Noise Level (approx.)	38 db
Timer (Optional)	No

### Salient Features\*



Preferred humidity settings



Easy roll castors



Auto humidity sensor



Extensive coverage area



Continuous drainage option



CFC free refrigerant



Auto stop with full tank indicator



Rotary compressor



European standards



\* Specific to models